



Security Defence Systems

Plot No. 50, DIC, Industrial Area , Baddi, Solan (H.P)

Web: www.sdschd.com

Email: rajeshmkt@yahoo.com

Phone: 0172-2632668

raghavendersahdev@gmail.com

Mobile: 09814014406

Fax: 0172-2633668

TOWER LIGHT 90 DEGREE ROTATION



MODEL : TOWER LIGHT 90 DEGREE ROTATION

Power Supply:	220V AC/ 380V AC at 50/60Hz.
Power Consumption:	2KW
Input Voltage:	220V AC/50Hz, 380V AC/60Hz.
Input Current:	10A.
Water proof grade:	IP54.
Lamp spec:	Xenon lamp 2KW.
Lamp life expectancy:	1000 hours.
Electric Resistance Intensity:	1.5KV
Insulation resistance:	more than 2M
Control Mode:	Stand-alone
Color effect:	White
Adjustment angle:	Pan Horizontal: 0° to 90° (automatic & adjustable) Tilt: 60° (adjustable)
Light beam angle:	0.6° – 0.8° (zoomable)
Range:	1-2 Km.
Remote control:	Range 20 meters.



Security Defence Systems

Plot No. 50, DIC, Industrial Area , Baddi, Solan (H.P)

Web: www.sdschd.com

Email: rajeshmkt@yahoo.com

Phone: 0172-2632668

raghavendersahdev@gmail.com

Mobile: 09814014406

Fax: 0172-2633668

TOWER LIGHT 440 DEGREE ROTATION



MODEL : TOWER LIGHT 440 DEGREE ROTATION

Power Supply:	220V AC/ 380V AC at 50/60Hz.
Power Consumption:	2KW
Input Voltage:	220V AC/50Hz, 380V AC/60Hz.
Input Current:	10A.
Water proof grade:	IP54.
Lamp spec:	Xenon lamp 2KW.
Lamp life expectancy:	1000 hours.
Electric Resistance Intensity:	1.5KV
Insulation resistance:	more than 2M
Control Mode:	Stand-alone
Color effect:	White
Adjustment angle:	Pan Horizontal: 0° to 440° (automatic & adjustable) Tilt: 60° (adjustable)
Light beam angle:	0.6° – 0.8° (zoomable)
Range:	1-2 Km.
Remote control:	Range 20 meters